

PILE DRIVERS

SG-45

FEATURES

- Designed to match the capabilities of larger excavators and to combine a robust structure with excellent pile handling characteristics.
- Fitted with heavy-duty arms/clamps capable of driving a wide range of piles including sheet piles, H-piles, tubular steel piles and other pile sections.
- High frequency pile driver with fixed eccentric moment.
- Based on the Movax Modular System (MMS™). The unit is always equipped with one of the standard arm/clamp systems and the bottom clamp. Customised arms and clamps are available upon special request.
- Controlled with the MOVAX Control System (MCS™); MCS Lite, MCS Pro or MCS Pro+auto.
- Available with M-logbook™ for documentation and reporting (optional, requires MCS Pro or MCS Pro+auto).



TECHNICAL DATA

Weight (excl. adapter) *	kg	2390
Height	mm	2530
Depth	mm	1180 - 1436
Width	mm	1193
Engine power, min	kW	100
Return pressure, max	bar	5
Pressure setting	bar	350
Frequency	1/min	2300 - 3000
Eccentric moment	kgm	4.6
Centrifugal force, max	kN	450
Ground vibration		Normal
Oil flow rate	l/min	0
Driving method		Vibration
Swing angle	°	+/- 360
Tilt angle	°	+/- 30
Auger diameter	mm	0

* with standard bottom clamp, exact weight depends on the side arm/clamp system

SUITABLE PILES

TYPES AND DIMENSIONS

Sheet pile	width mm	400-1200
	depth mm	265
H-beam	size	H180-H500
Timber pile	mm	Ø 160-420
Tubular pile, tubes *	mm	up to 762

* up to 1220 mm diameter with modular tube arms and tandem bottom clamp



LENGTH & WEIGHT

8m / 2300kg
12m / 1600kg
16m / 1200kg